2026 Ford Maverick® Truck

TECHNICAL SPECIFICATIONS

7/20/26 v. 1.2



BODY INFORMATION

Body style	Unibody SuperCrew® pickup
Frame construction	High-strength steel frame
Body material	Steel body panels and aluminum hood
Trim levels	XL, XLT, Lobo™, Lariat®, Tremor®
Final assembly location	Hermosillo Assembly Plant, Sonora, Mexico

DRIVETRAIN

Standard	Front engine, hybrid, front-wheel drive (FWD) with PowerSplit continuously variable transmission
Optional	Front engine, internal combustion engine (ICE) FWD/all-wheel drive (AWD) with 8-Speed automatic transmission (7-speed with Lobo)
	Front engine, hybrid, AWD with PowerSplit continuously variable transmission

ENGINE SPECS AND KEY FEATURES

	2.5L Hybrid	2.0L EcoBoost® I-4
Horsepower[1] (@ rpm)	184[2] (combined)	250 @ 5,500[3]
Torque[1] (lb.-ft. @ rpm)	—	280 @ 3,000[3]
Electric Motor Output (lb.-ft. of torque)	236	—
Available Maximum Conventional Towing[1][4] (lbs.)	4,000[5]	4,000[5]
Available Maximum Payload[1][6] (lbs.)	1,500	1,500
Configuration	In-line 4-cylinder, Atkinson-Cycle	In-line 4-cylinder, dual overhead cam
Induction	Naturally aspirated	Single twin-scroll turbocharged
Intake Manifold Material	Composite	Composite
Exhaust Manifold	Fabricated steel	Integrated
Engine Block Material	Aluminum	Aluminum
Cylinder Head Material	Aluminum	Aluminum
Piston Material	Aluminum	Aluminum
Crankshaft	Forged steel	Forged steel
Connecting Rod Material	Powder forged steel	Powder forged steel
Displacement (liters/cubic inches)	2.5/152	2.0/122
Bore x Stroke (inches)	3.50 x 3.94	3.31 x 3.54
Compression Ratio (:1)	13.0	10.8
Valvetrain	DOHC, iVCT	DOHC, Ti-VCT
Fuel Delivery	Sequential multiport fuel injection	Port fuel and direct-injection (PFDI)
Recommended unleaded fuel (minimum)	Regular 87 octane	Premium 91+ octane
Oil Capacity (quarts)	5.7	6.1
Coolant Capacity (quarts)	9.6 (gas)/5.0 (electric)	9.2/9.5 (with 4K Tow Package)

(1) Horsepower, torque, payload, towing and EPA-estimated fuel economy ratings are independent attributes and may not be achieved simultaneously.
(2) Calculated via combined performance of the engine and electric motor with peak battery power. The calculations utilize SAE Net J1349 engine results and Ford electric motor dyno testing. Your results may vary.
(3) Horsepower and torque ratings are based on premium fuel per SAE J1349® standard. Your results may vary.
(4) When properly equipped. Maximum towing varies based on cargo, vehicle configuration, accessories, and number of passengers.
(5) Requires extra-cost 4K Tow Package (53Q).
(6) Maximum payload varies and is based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.

HYBRID SYSTEM

Configuration	2.5L Hybrid powertrain only
Electric Motor Type	Permanent magnet electric traction (Ford in-house E_Motor)
Output	94 kW/173 lb.-ft. battery peak
Battery Cooling System	Liquid
Battery Location	Passenger side, under cabin

TRANSMISSION SPECIFICATIONS

2.5L Hybrid PowerSplit electronic continuously variable transmission (eCVT)

2.0L EcoBoost 8-speed automatic; 7-speed automatic with paddle shifters (Lobo only)

Gear Ratios (:1)	PowerSplit eCVT	8-speed automatic	7-speed automatic (Lobo)
First	Not Applicable	4.69	4.69
Second	Not Applicable	3.31	3.01
Third	Not Applicable	3.01	1.92
Fourth	Not Applicable	1.92	1.45
Fifth	Not Applicable	1.45	1.00
Sixth	Not Applicable	1.00	0.75
Seventh	Not Applicable	0.75	0.62
Eighth	Not Applicable	0.62	—
Final Drive	3.37	3.63/3.81 (4K Tow only)	3.63
Reverse	Not Applicable	2.96	2.96

FUEL TANK CAPACITY

Drivetrain	Capacity (gallons)
2.5L Hybrid	13.8
2.0L EcoBoost I-4	16.5

FUEL ECONOMY RATINGS

EPA-Estimated Ratings[1]			
Engine/Transmission	**City**	**Highway**	**Combined**
2.0L EcoBoost I-4/7-speed automatic (Lobo 4WD)	21	30	24
2.0L EcoBoost I-4/8-speed automatic (FWD)	23	32	26
2.0L EcoBoost I-4/8-speed automatic (AWD)	22	30	25
2.0L EcoBoost I-4/8-speed automatic (Tremor 4WD)	21	27	23
2.5L Atkinson-cycle I-4/eCVT — hybrid (FWD)	42	35	38
2.5L Atkinson-cycle I-4/eCVT — hybrid (AWD)	40	34	37
2.5L Atkinson-cycle I-4/eCVT — hybrid (Lariat AWD)	39	32	36

(1) Actual mileage will vary.

SUSPENSION

Front Configuration	Independent MacPherson strut-type suspension with coil springs, twin-tube hydraulic gas-pressurized shock absorbers, stabilizer bars, aluminum lower control arm, steel sub-frame and cast knuckle
Rear Configuration (FWD drivetrain)	Independent twist-beam rear suspension with integrated stabilizer bar, Ford-patented “force vectoring" springs, twin-tube hydraulic gas-pressurized shock absorbers
Rear Configuration (AWD drivetrain)	Independent multi-link trailing arm suspension with twin-tube hydraulic gas-pressurized shock absorbers, coil springs, stabilizer bar, steel sub-frame and cast knuckle
Rear Configuration (AWD/FX4®) – Lobo and Tremor	Independent multi-link trailing arm suspension with mono-tube hydraulic gas pressurized shock absorbers with hydraulic rebound stop, coil springs, stabilizer bar, steel sub-frame and cast knuckle

STEERING

Type Electronic power-assisted rack-and-pinion

Configurations	Steering Ratio (:1)	Turning Diameter (feet, curb-to-curb)
All	16.3	40.0

BRAKES

	2.5L Hybrid	2.0L EcoBoost I-4
System Type – Standard	4-wheel disc brakes with ABS and regenerative braking	4-wheel disc brakes with ABS
System Type – Available	Not Available	Upgraded front brakes with two piston calipers, larger brake rotor, larger brake pads (Lobo only)

EXTERIOR DIMENSIONS (inches unless otherwise noted)

	2.5L Hybrid FWD	2.5L Hybrid AWD	2.0L EcoBoost FWD	2.0L EcoBoost AWD	Tremor AWD	Lobo AWD
Wheelbase	121.1	121.1	121.1	121.1	121.1	121.1
Vehicle Length	199.8	199.8	199.8	199.8	200.6	200.9
Vehicle Height (maximum)	68.8	68.3	68.9	68.5	69.4	67.7
Vehicle Width (at the door handles)	72.6	72.6	72.6	72.6	72.6	72.6
Body Width (maximum)	72.4	72.4	72.4	72.4	72.4	72.4
Vehicle Width (including mirrors)	83.5	83.5	83.5	83.5	83.5	83.5
Vehicle Width (mirrors folded)	77.9	77.9	77.9	77.9	77.9	77.9
Track Width – Front (curb)	63.6	63.7	63.4	63.5	63.1	63.7
Track Width – Rear (curb)	63.0	62.7	62.7	62.6	62.4	63.1
Overhang – Front	34.2	34.2	34.2	34.2	34.4	34.7
Overhang – Rear	44.5	44.5	44.5	44.5	45.1	45.0
Angle of Approach (degrees)	20.3	20.4	20.1	21.1	30.8	19.0
Angle of Departure (degrees)	22.2	21.0	22.4	21.1	21.6	19.3
Ramp Breakover Angle (degrees)	16.7	15.9	18.1	18.3	20.1	17.0
Minimum Running Ground Clearance	8.1	8.1	8.0	8.3	9.1	7.4
Front Bumper to Back of Cab	137.7	137.7	137.7	137.7	138.0	138.2
Lift-in Height (tailgate to ground)	30.4	29.4	30.5	29.4	30.0	28.2

CARGO BOX SPECIFICATIONS (inches unless otherwise noted)

	2.5L Hybrid	2.0L EcoBoost	Tremor	Lobo
Pickup Body Height	20.3	20.3	20.3	20.3
Pickup Body Length – at Floor	54.4	54.4	54.4	54.4
Pickup Body Length – Top of Body	53.1	53.1	53.1	53.1
Rear Opening Width – Top of Box or Belt	49.8	49.8	49.8	49.8
Rear Opening Width – Lower	48.8	48.8	48.8	48.8
Cargo Width, Wheelhouse	42.6	42.6	42.6	42.6
Exposed Cargo Width	53.3	53.3	53.3	53.3
Cargo Box Volume (cu. ft.)	33.3	33.3	33.3	33.3

INTERIOR DIMENSIONS (inches unless otherwise noted)

	Front	Rear
Head Room	40.2	39.6
Head Room (with moonroof)	38.0	39.4
Maximum Leg Room (hybrid/gas)	42.8/42.8 (accelerator)	35.9/36.9
Shoulder Room	57.3	55.6 (beltline)
Hip Room	55.4	54.1

INTERIOR VOLUME (cubic feet)

	2.5L Hybrid	2.0L EcoBoost
Interior Volume	100.3	101.5
Volume – First Seat Compartment	54.5	54.5
Volume – First Seat Compartment (with moonroof)	51.4	51.4
Volume – Rear Seat Compartment	45.8	47.1
Volume – Rear Underseat Storage	2.0	2.6

WEIGHTS (pounds)

	2.5L Hybrid FWD	2.5L Hybrid AWD	2.0L EcoBoost FWD	2.0L EcoBoost AWD	Tremor AWD	Lobo AWD
Base Curb Weight	3,667	3,838	3,517	3,652	3,890	3,814
Gross Vehicle Weight Rating (GVWR)	5,230	5,330	5,100	5,240	5,090	4,970
Maximum Payload[1]	1,500	1,400	1,500	1,500	1,140	1,045
Maximum Towing[2] (standard/optional)	2,000	2,000/ 4,000[3]	2,000	2,000/ 4,000[3]	2,000	2,000

(1) Maximum payload varies and is based on accessories and vehicle configuration. See label on doorjamb for carrying capacity of a specific vehicle. Always properly secure cargo.

(2) When properly equipped. Maximum towing varies based on cargo, vehicle configuration, accessories, and number of passengers.

(3) Requires extra-cost 4K Tow Package (53Q).

WHEELS

Standard
17" Sparkle Silver-painted steel (XL)
17" Carbonized Gray-painted aluminum (XLT)
17" machined-face Dark Tarnish-painted aluminum with orange-painted pocket (Tremor)
19" painted aluminum (Lariat)
19" black-painted, turbofan-styled aluminum (Lobo)
Optional
19" black-painted aluminum (included in Black Appearance Package; optional on Lobo)

TIRES

Standard
225/65R17 all-season (XL, XLT)
235/65R17 all-terrain (Tremor)
225/55R19 all-season (Lariat and Lobo; included in Black Appearance Package)
Optional
225/65R17 all-terrain (included in FX4 Off-Road Package)
Spare: 215/70R17 all-terrain (included in 4K Tow Package; standard on Tremor)

WARRANTY

Bumper-to-bumper	3 years/36,000 miles
Powertrain	5 years/60,000 miles
Hybrid/Electric Unique Components	8 years/100,000 miles
Aluminum body panels	5 years/unlimited miles
Corrosion – sheet metal (perforation only; excludes aluminum)	5 years/unlimited miles
Paint adhesion	5 years/unlimited miles
Roadside assistance	5 years/60,000 miles